



GRAPHENSTONE®

The perfect solution for
heritage, restoration
and lime

Exceptional
Heritage Paints



GRAPHENSTONE®

Graphenstone UK Head Office
15 - 16 G Speedwell Way, Border Valley Industrial Estate,
Harleston, Norfolk, IP20 9EH

www.graphenstone.co.uk | info@graphenstone.co.uk | +44 (0) 1379 772 940



Perfect for Lime



Excellent
★★★★★
TRUSTPILOT

Exceptional Heritage Paints

Traditional building materials like lime and clay have been used to decorate and protect buildings inside and out for thousands of years. In the past, this meant using a limewash or other more delicate materials such as distempers.

These coatings, whilst allowing the substrate to breathe effectively, were often more difficult to use, lacked durability, and offered a limited lifespan compared to modern plastic based paints.

These materials are still present in many older buildings and are now widely used as a more sustainable option for renovation and modern construction.

Graphenstone lime silicate paints offer the best of both

STEP 1 - PREPARATION

Ensure that surfaces are clean, dry, sound and free of contaminants.

STEP 2 - PRIMER COAT

Apply 1 x coat of Ambient Primer L42 (diluted 1:1 with water).

STEP 3 - TOP COATS

Apply 2 x coats of GCS paint (diluted 10-15% with water).

Graphenstone GCS

It is important to apply the correct type of decorative and protective materials; this means applying a fully breathable paint.

GCS is an easy to use, highly breathable paint with excellent opacity and coverage. The durable alternative to conventional heritage paints such as limewash and distemper.

Graphenstone GCS is a perfect choice for interior and exterior lime plasters, renders, and other mineral substrates eg: stone, clay & brick.

Technical information

| | |
|-----------------------|---|
| Area of use: | Available for interior and exterior use |
| Finish: | Flat matt (2% sheen) |
| Durable : | Class 1 |
| Colours: | Available in a large range of colours |
| Breathability: | Class 1 |
| Toxin free: | Trace VOCs <0.1% |
| Coverage: | 10 - 16m ² / litre / coat (depending on substrate) |
| Cleaning: | Water based |
| Drying: | Between coats: 2 - 4 hours |
| Total drying: | 24 hours |

