The perfect solution for heritage, restoration and lime



GRAPHENSTONE®

Exceptional Heritage Paints



GRAPHENSTONE®

Graphenstone UK Head Office 15 - 16 G Speedwell Way, Border Valley Industrial Estate, Harleston, Norfolk, IP20 9EH

www.graphenstone.co.uk | info@graphenstone.co.uk | +44 (0) 1379 772 940





Perfect for Lime

Please scan the QR for full application and technical details

۲

۲

 $(\mathbf{ }$

Exceptional Heritage Paints

Traditional building materials like lime and clay have been used to decorate and protect buildings inside and out for thousands of years. In the past, this meant using a limewash or other more delicate materials such as distempers.

These coatings, whilst allowing the substrate to breathe effectively, were often more difficult to use, lacked durability, and offered a limited lifespan compared to modern plastic based paints.

These materials are still present in many older buildings and are now widely used as a more sustainable option for renovation and modern construction.

> Graphenstone lime silicate paints offer the best of both

STEP 1 - PREPARATION Ensure that surfaces are clean, dry, sound and free of contaminants.

STEP 2 - PRIMER COAT Apply 1 x coat of Ambient Primer L42 (diluted 1:1 with water).

STEP 3 - TOP COATS Apply 2 x coats of GCS Heritage paint (diluted 10-15% with water).

Graphenstone GCS

It is important to apply the correct type of decorative and protective materials; this means applying a fully breathable paint.

GCS is an easy to use, highly breathable paint with excellent opacity and coverage. The durable alternative to conventional heritage paints such as limewash and distemper.

Graphenstone GCS is a perfect choice for interior and exterior lime plasters, renders, and other mineral substrates eg: stone, clay & brick.

Technical information

rea of use:	Available for interior and exterior use	
nish:	Flat matt (2% sheen)	
urable :	Class 1	
olours:	Available in a large range colours	
eathability:	Class 1	
xin free:	Trace VOCs <0.1%	
overage:	10 - 16m² / litre / coat (depending on substrat	te)
eaning:	Water based	
rying:	Between coats: 2 - 4 hours	
otal drying:	24 hours	



Please scan the QR for full application and technical details